

FORMATS BARRES PTFE MOULEES

Diamètre	Tolérance
30*	+1,2-0
35*	+1,6-0
40*	+1,6-0
45	+2,0-0
50	+2,0-0
55	+2,4-0
60	+2,4-0
65	+2,8-0
70	+2,8-0
75	+3,2-0
80	+3,2-0
85	+3,6-0
90	+3,6-0
95	+4,0-0
100	+4,0-0
105	+5,0-0
110	+5,0-0
115	+5,0-0
120	+5,0-0
125	+5,0-0
130	+5,0-0
135	+5,0-0
140	+5,0-0
145	+5,0-0
150	+5,0-0
155	+6,0-0
160	+6,0-0
165	+6,0-0
170	+6,0-0
175	+6,0-0
180	+6,0-0
185	+6,0-0
190	+6,0-0
195	+6,0-0
200	+6,0-0
205	+6,0-0
210	+6,0-0
215	+6,0-0
220	+6,0-0
225	+6,0-0
230	+6,0-0
235	+6,0-0
240	+6,0-0

Diamètre	Tolérance
245	+6,0-0
250	+6,0-0
255	+6,0-0
260	+6,0-0
265	+6,0-0
270	+6,0-0
280	+6,0-0
285	+6,0-0
290	+6,0-0
300	+6,0-0
310	+6,0-0
315	+6,0-0
320	+8,0-0
330	+8,0-0
335	+8,0-0
340	+8,0-0
345	+8,0-0
350	+8,0-0
365	+8,0-0
380	+10,0-0
395	+10,0-0
400	+10,0-0
410	+10,0-0
420	+12,0-0
435	+12,0-0
450	+12,0-0
460	+12,0-0
470	+12,0-0
480	+12,0-0
500	+12,0-0
525	+12,0-0
540	+12,0-0
560	+12,0-0
585	+12,0-0
600	+12,0-0
620	+12,0-0
635	+12,0-0
650	+12,0-0
690	+12,0-0
700	+15,0-0
720	+15,0-0
750	+15,0-0
770	+15,0-0

Tolérance de longueur +15mm-0

Approflon - Juin 2015

* Longueur maximum 200 mm

Données non contractuelles

De 30 à 400 mm de diamètre : longueur maxi 300 mm

+ de 400 mm : longueur maxi 80 ou 100mm